Split System Inverter Reverse Cycle air conditioner, DC fan motor with 12 fan speeds, concealed dimmable digital display, HEPA and ion filters, auto swing (up, down), LCD remote, DRED capable. 5.0kW cooling/6.0kW heating capacity & with 3.5 Energy Star Rating

RRP AUS $1,549.00

Product Details

FEATURES

Heating and cooling modes of operation
Provides year round comfort

Auto or Manual operation
Easy to set and forget or retain full user control

LCD backlit wireless remote control
Easy access to all functionality combined with a large easy screen backlit to be clearly readable in all lighting conditions

Follow Me command
Measures and controls the temperature where you are for personal comfort

24 hour timer
Program your air conditioner to turn on and off automatically

Auto restart
In the event of an interruption in power supply the unit will restart with the same settings that were selected prior to the power outage

Inverter compressor technology
Electronic compressor control for maximum energy efficiency and minimum noise

Up to 5 year comprehensive residential warranty

Auto Air Swing
Air can be automatically directed up and down to distribute cooling or heating evenly

Sleep mode
Sleep mode automatically adjusts the temperature while you sleep for maximum comfort and minimum energy consumption

BENEFITS

Peace of mind
BioFresh filtration is the ideal way to purify, sterilise and deodorise the air in your living areas

Superior comfort and control
With DC inverter technology you'll enjoy greater comfort, control and energy efficiency all year round

Easy to use
One touch climate control is at your fingertips with a simple-to-use remote control

Easy to clean
The contemporary clean-face fascia not only looks good, it also minimises dust build-up on the front of the unit. Slim and compact, these air-conditioners are unobtrusive and will suit any interior style

Specifications

PRODUCT PROFILE

Domestic warranty details (yrs)	5
Type	reverse cycle

SPECIFICATIONS

Nominal horsepower	2.0
Capacity cool watts	5000
Capacity cool Btu/h	17100
Capacity Heat watts	6000
Capacity Heat Btu/h	20500
Current rating amps	15.5
Power Supply Connection Point	outdoor unit
Colour of fascia	White, Digital Display
Compressor type	rotary
Indoor sound pressure dBA high setting	49
Indoor sound pressure dBA low setting	32
Outdoor sound pressure dBA	60
Outdoor Sound Power dBA	64

SPECIFICATIONS

Indoor air circulation max (ltr/s)	333
Ambient temperature range minimum	-15
Ambient temperature range maximum	50
Moisture removal ltr/hour	1.9
New Energy star rating cooling	3.5
New Energy star rating heating	3.5
Cooling EER	4.0
Heating COP	4.0
Refrigerant weight (g)	1450
Refrigerant type	R32

OUTDOOR UNIT DIMENSIONS

Width (mm)	924
Height (mm)	702
Depth (mm)	382

INDOOR UNIT DIMENSIONS

Total width (mm)	1080
Total height (mm)	335
Total depth (mm)	226

FEATURES

Filtration	dust,hepa,Ion Filter
Remote control type	LCD,back lit
Timer	24 hour
Anti corrosion treatment	gold
Fan speeds	low,medium,high,turbo,Auto,Silent

INSTALLATION REQUIREMENTS (PIPING AND WIRING)

Gas pipe size	12.7
Liquid pipe size	6.35
Maximum piping length vertical	20
Maximum piping length	30
Additional refrigerant required supplied charge length (g/m)	15
Maximum pipe length with supplied charge	5
Wires connecting indoor unit to outdoor unit	4

INDOOR UNIT PACKED DIMENSIONS

Shipping Volume (m3)	0.15
Shipping Weight (Kg)	17.5
Pack Dimensions Width (mm)	1155
Pack Dimension Height (mm)	415

OUTDOOR UNIT PACKED DIMENSIONS

Shipping Volume (m3)	0.29
Shipping Weight (Kg)	47.2
Pack Dimensions Width (mm)	965
Pack Dimension Height (mm)	765

INDOOR UNIT PACKED DIMENSIONS

Pack Dimension Depth (mm)	315

OUTDOOR UNIT PACKED DIMENSIONS

Pack Dimension Depth (mm)	395

STUFFING QUANTITIES

20ft	56
40ft	112
40ft HC	126

Terms and Conditions

IMPORTANT

This is a guide of product dimensions only. For complete installation instructions, refer to the manual provided with product.

PRODUCT INFORMATION

The descriptors and illustrations in this publication apply to the specific products and models described as at the date of issue. Under our policy of continuous productdevelopment, product specifications may change without notice. Prospective purchasers should therefore check with their retailer to ensure this publication correctly describes theproducts that are being offered for sale. All information supplied is to be used for general reference purposes only and is on the understanding that Electrolux Home Products PtyLtd (Australia) and Electrolux (NZ) Ltd (New Zealand) will not be liable for any loss, liability or damage of whatever kind arising as a result of reliance on such information. Colours ofproducts illustrated are as close as printing limitations allow. Electrolux will at all times comply with its obligations pursuant to law including Trade Practices (Australian Consumer Law) Act and Regulations.

WARRANTY

This warranty only applies to Appliances purchased and used in Australia or New Zealand and used in normal domestic applications and is in addition to (and does not exclude, restrict, or modify in any way) any non-excludable statutory warranties in Australia or New Zealand. All warranties are subject to the conditions set out in the warranty card accompanying the product when purchased.

ELECTROLUX HOME PRODUCTS AUSTRALIA
telephone: 1300 363 640
fax: 1800 350 067
email: customercare@electrolux.com.au
web: www.electrolux.com.au

ELECTROLUX HOME PRODUCTS NEW ZEALAND
telephone: 09 573 2230
fax: 09 573 2221
email: customercare@electrolux.co.nz
web: www.electrolux.co.nz